

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **Antisilikon-Lösung für Wasserlacke** **8117b:**

Product number 90693

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Additive for water-based coating materials; for industrial or professional end-uses.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:ADLER-Werk Lackfabrik Johann Berghofer GmbH & Co KG
Bergwerkstraße 22
A-6130 Schwaz
AustriaFurther information obtainable from: sdb-info@adler-lacke.comTelephone
+43 5242 6922-713
Mon - Thu 07:00 AM - 04:25 PM
Fri 07:00 AM - 12:15 PM

1.4 Emergency telephone number

Country	Name	Telephone
United Kingdom	Guy's & St Thomas' Poisons Unit	+44 (0)20 7188 0100

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard class and category	Hazard statement
skin corrosion/irritation	2	Skin Irrit. 2	H315
serious eye damage/eye irritation	2	Eye Irrit. 2	H319

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- Signal word warning

- Pictograms

GHS07



- Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26

- Precautionary statements

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Surfactant in organic solvents and water.

Name of substance	Identifier	Wt%	Classification acc. to GHS
2-butoxyethanol	CAS No 111-76-2 EC No 203-905-0 Index No 603-014-00-0 REACH Reg. No 01-2119475108-36-xxxx	5 - < 10	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319
perfluoroalkyl substituted polyether	EC No 615-036-8	5 - < 10	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335
(2-methoxymethylethoxy)propanol	CAS No 34590-94-8 EC No 252-104-2 REACH Reg. No 01-2119450011-60-xxxx 01-2119991100-47-xxxx	1 - < 3	

For full text of abbreviations: see SECTION 16.

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26:

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Take off immediately all contaminated clothing. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Following inhalation

Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician.

Following skin contact

Take off contaminated clothing. After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Do not use any solvents or thinners!

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Keep at rest. IF SWALLOWED: Immediately call a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), BC-powder, Water spray, Alcohol resistant foam, Sand

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Thick smoke may occur in case of a fire. Inhaling the decomposed products may cause serious damage to health. The formation of explosive dust-air-mixtures is possible. Upon contact with air, the vapours may form an explosive mixture. . Combustible.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26:

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Provision of sufficient ventilation. Control of dust.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Dilute with plenty of water.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains, Fill contaminated material in the original container or any other suitable one and dispose it in accordance with point 13.

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feed-stuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Flammability hazards

Keep away from sources of ignition - No smoking. Ground/bond container and receiving equipment.

Control of effects

Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. . Close the open container carefully and keep it straight to prevent leakage.

Store in the original container. Storage temperature of 0 °C/32 °F and up to 50 °C/122 °F.

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26:

Protect against external exposure, such as

Frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
EU	2-butoxyethanol	111-76-2	IOEL V	20	98	50	246				2000/39/EC
EU	(2-methoxy-methylethoxy)propanol	34590-94-8	IOEL V	50	308						2000/39/EC
GB	2-butoxyethanol	111-76-2	WEL	25	123	50	246				EH40/2005
GB	(2-methoxy-methylethoxy)propanol	34590-94-8	WEL	50	308						EH40/2005

Notation

Ceiling-C

STEL

TWA

ceiling value is a limit value above which exposure should not occur
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
GB	2-butoxyethanol	2-butoxyacetic acid	crea	BMGV	240 mmol/mol	EH40/2005

Notation

crea creatinine

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-butoxyethanol	111-76-2	DNEL	98 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-butoxyethanol	111-76-2	DNEL	1,091 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
2-butoxyethanol	111-76-2	DNEL	246 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26:

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-butoxyethanol	111-76-2	DNEL	125 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-butoxyethanol	111-76-2	DNEL	89 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
(2-methoxymethyl-ethoxy)propanol	34590-94-8	DNEL	308 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
(2-methoxymethyl-ethoxy)propanol	34590-94-8	DNEL	283 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2-butoxyethanol	111-76-2	PNEC	8.8 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-butoxyethanol	111-76-2	PNEC	0.88 mg/l	aquatic organisms	marine water	short-term (single instance)
2-butoxyethanol	111-76-2	PNEC	463 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-butoxyethanol	111-76-2	PNEC	34.6 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-butoxyethanol	111-76-2	PNEC	3.46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-butoxyethanol	111-76-2	PNEC	2.33 mg/kg	terrestrial organisms	soil	short-term (single instance)
(2-methoxymethyl-ethoxy)propanol	34590-94-8	PNEC	19 mg/l	aquatic organisms	freshwater	short-term (single instance)
(2-methoxymethyl-ethoxy)propanol	34590-94-8	PNEC	1.9 mg/l	aquatic organisms	marine water	short-term (single instance)
(2-methoxymethyl-ethoxy)propanol	34590-94-8	PNEC	4,168 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
(2-methoxymethyl-ethoxy)propanol	34590-94-8	PNEC	70.2 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
(2-methoxymethyl-ethoxy)propanol	34590-94-8	PNEC	7.02 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
(2-methoxymethyl-ethoxy)propanol	34590-94-8	PNEC	2.74 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26

Individual protection measures (personal protective equipment)

Eye/face protection

Use safety goggles with side protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Use rubber or polyvinyl chloride gloves for protection against liquid splashes during brief working operations.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment. Combination filtering device (EN 141). Particulate filter device (EN 143). Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Colour	opaque
Odour	specific type

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	not determined
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	this information is not available
Vapour pressure	23 hPa at 20 °C
Density	1.01 g/cm ³ at 20 °C

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26

Vapour density	this information is not available
Solubility(ies)	
- Water solubility	miscible in any proportion
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	not applicable
Viscosity	
- Kinematic viscosity	10 – 12 ^s / _{DIN 4mm} at 20 °C
Explosive properties	not explosive
Oxidising properties	none

9.2 Other information

Solid content	5 % ± 1,0 %
---------------	-------------

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
2-butoxyethanol	111-76-2	oral	1,414 mg/kg
2-butoxyethanol	111-76-2	dermal	1,100 mg/kg
2-butoxyethanol	111-76-2	inhalation: vapour	11 mg/l/4h
perfluoroalkyl substituted polyether		oral	500 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26:

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes, Decision 2000/532/EC on the list of waste

- Product

08 01 15x aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

- Packagings

15 01 10x packaging containing residues of or contaminated by dangerous substances

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	not subject to transport regulations
14.2	UN proper shipping name	not relevant
14.3	Transport hazard class(es)	none
14.4	Packing group	not assigned to a packing group
14.5	Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)

Not subject to ADR, RID and ADN.

International Maritime Dangerous Goods Code (IMDG)

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR)

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

Deco-Paint Directive (2004/42/EC)

VOC content	12.4 % 130 g/l
-------------	-------------------

Directive on industrial emissions (VOCs, 2010/75/EU)

VOC content	12.4 % 125.2 g/l
-------------	---------------------

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

none of the ingredients are listed

Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Directive 2000/60/EC establishing a framework for Community action in the field of water policy (WFD)

none of the ingredients are listed

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26

Regulation 98/2013/EU on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation 111/2005/EC laying down rules for the monitoring of trade between the Community and third countries in drug precursors

none of the ingredients are listed

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")

Antisilikon-Lösung

Version number: 8.1

Revision: 2019-03-26
Date of issue: 2019-03-26

Abbr.	Descriptions of used abbreviations
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
SVHC	Substance of Very High Concern
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

Note concerning the lower explosion limit of water-thinnable varnishes:

See PTB research report PEx5 200500185, Physical-Technical Federal Agency Braunschweig, September 2005 and report PTB-W-57, February 1994.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.