

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **PUR-Hardener 8429** **8429a:**
Product number 8429000210

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Hardener for solvent-based coating materials;
for industrial or professional end-uses.
Uses advised against Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

ADLER-Werk Lackfabrik Johann Berghofer GmbH & Co KG
Bergwerkstraße 22
A-6130 Schwaz
Austria

Telephone: +4352426922713
e-mail: sdb-info@adler-lacke.com

Further information obtainable from: sdb-info@adler-lacke.com

Telephone
+43 5242 6922-713
Mon - Thu 07:00 AM - 04:25 PM
Fri 07:00 AM - 12:15 PM

1.4 Emergency telephone number

Country	Name	Telephone
United Kingdom	Guy's & St Thomas' Poisons Unit	+44 (0)20 7188 0100

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (acc. to GB CLP)

Hazard class	Category	Hazard class and category	Hazard statement
flammable liquid	3	Flam. Liq. 3	H226
skin sensitisation	1	Skin Sens. 1	H317
specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08

Labelling (acc. to GB CLP)

- Signal word warning

- Pictograms

GHS02, GHS07



- Hazard statements

H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist/vapours/spray.
P280 Wear protective gloves/eye protection/face protection.
P312 Call a POISON CENTRE/doctor/... if you feel unwell.
P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH204 Contains isocyanates. May produce an allergic reaction.

- Hazardous ingredients for labelling hexamethylene-1,6-diisocyanate, oligomers

2.3 Other hazards

Keep out of reach of children and do not empty into the drains. Dispose remainders properly (collection of hazardous waste, disposal companies). Empty containers must be entered into the recycling system. The usual safety precautions must be observed during processing of the product.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not relevant (mixture)

3.2 Mixtures

Description of the mixture Aliphatic polyisocyanate resin in organic solvents.

Name of substance	Identifier	Wt%	Classification acc. to GHS
hexamethylene-1,6-diisocyanate, oligomers	CAS No 28182-81-2 EC No 500-060-2 931-274-8	25 - < 50	Acute Tox. 3 / H331 Skin Sens. 1 / H317 STOT SE 3 / H335

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08:

Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
hexamethylene-1,6-diisocyanate, oligomers	-	-	0.543 mg _v /l/4h	inhalation: dust/ mist

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Take off immediately all contaminated clothing. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Following inhalation

Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician.

Following skin contact

Take off contaminated clothing. After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Do not use any solvents or thinners!.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Keep at rest. IF SWALLOWED: Immediately call a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), BC-powder, Water spray, Alcohol resistant foam, Sand

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Thick smoke may occur in case of a fire. Inhaling the decomposed products may cause serious damage to health. The formation of explosive dust-air-mixtures is possible. Upon contact with air, the vapours may form an explosive mixture. . Combustible.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08:

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Provision of sufficient ventilation. Control of dust.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains, Fill contaminated material in the original container or any other suitable one and dispose it in accordance with point 13.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feed-stuffs.

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08:

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Protect from sunlight.

Control of effects

Do not pierce or burn, even after use. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Close the open container carefully and keep it straight to prevent leakage. Store in the original container. Storage temperature of 0 °C/32 °F and up to 50 °C/122 °F.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
EU	n-butyl acetate	123-86-4	IOEL V	50	241	150	723				2019/1831/EU
GB	butyl acetate	123-86-4	WEL	150	724	200	966				EH40/2005

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur
STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
hexamethylene-1,6-diisocyanate, oligomers	28182-81-2	DNEL	0.5 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08:

Relevant DNELs of components						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
hexamethylene-1,6-diisocyanate, oligomers	28182-81-2	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
hexamethylene-1,6-diisocyanate, oligomers	28182-81-2	PNEC	0.127 mg/l	aquatic organisms	freshwater	short-term (single instance)
hexamethylene-1,6-diisocyanate, oligomers	28182-81-2	PNEC	0.013 mg/l	aquatic organisms	marine water	short-term (single instance)
hexamethylene-1,6-diisocyanate, oligomers	28182-81-2	PNEC	88 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
hexamethylene-1,6-diisocyanate, oligomers	28182-81-2	PNEC	266,701 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
hexamethylene-1,6-diisocyanate, oligomers	28182-81-2	PNEC	26,670 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
hexamethylene-1,6-diisocyanate, oligomers	28182-81-2	PNEC	53,183 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Use safety goggle with side protection (EN 166).

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Use protective gloves made of butyl rubber as spray protection for short-term work. Material strength: 0.5mm, penetration time ≥ 480 min.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08

Respiratory protection

During spraying wear suitable respiratory equipment. Combination filtering device (EN 141). Particulate filter device (EN 143). Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless clear
Odour	characteristic
Melting point/freezing point	<-90 °C
Boiling point or initial boiling point and boiling range	126.2 °C at 1,013 hPa
Flammability	flammable liquid in accordance with GHS criteria

Lower and upper explosion limit

Lower explosion limit (LEL)	1.2 vol%
Upper explosion limit (UEL)	10.4 vol%
Flash point	28 °C
Auto-ignition temperature	415 °C
pH (value)	not determined
Kinematic viscosity	10 – 12 ^S / _{DIN 4mm}

Solubility(ies)

Water solubility	not miscible in any proportion
------------------	--------------------------------

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	10.15 hPa at 18.49 °C
-----------------	-----------------------

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08

Density and/or relative density

Density	0.9845 g/cm ³ at 20 °C
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

Other safety parameters

Explosive properties	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
----------------------	---

9.2 Other information

Information with regard to physical hazard classes	there is no additional information
Other safety characteristics	there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if inhaled.

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
hexamethylene-1,6-diisocyanate, oligomers	28182-81-2	inhalation: dust/mist	0.543 ^m g/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Other information

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08:

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes

- Product

08 05 01* waste isocyanates

- Packagings

15 01 10* packaging containing residues of or contaminated by hazardous substances

Disposal methods:

Product

Waste production should be avoided or minimised if possible.

Do not empty into the drains. Avoid releasing the product into the environment. Waste, containers must be removed, disposed in a safe way.

Packagings

Waste production should be avoided or minimised if possible.

Packaging waste should be recycled. Burning or landfilling should only be considered if recycling is not feasible.

Notes on disposal:

Product

Disposal of this product and its dissolutions and by-products must be carried out in accordance with the environmental protection requirements and waste disposal laws as well as the requirements of the local authorities at all times. Excess must be handed over, disposed to a recognised waste disposal company (disposal company/recycling company).

Packagings

With the aid of the information provided in this safety data sheet, the responsible authorities must be consulted regarding classification of empty containers, packaging. Empty containers should be disposed, recycled according to type. Licenced containers, packaging can be disposed free of charge via system partners, where applicable. Containers with residual contents must be disposed in accordance with local and national legal provisions.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08:**SECTION 14: Transport information****14.1 UN number**

ADR/RID	UN 1123
IMDG-Code	UN 1123
ICAO-TI	UN 1123

14.2 UN proper shipping name

ADR/RID	BUTYL ACETATES
IMDG-Code	BUTYL ACETATES
ICAO-TI	Butyl acetates

14.3 Transport hazard class(es)

ADR/RID	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

ADR/RID	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations**Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) - Additional information**

Classification code	F1
Danger label(s)	3



Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	D/E
Hazard identification No	30
Emergency Action Code	3Y

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08:

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) - Additional information

Classification code F1

Danger label(s) 3



Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

Transport category (TC) 3

Hazard identification No 30

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant -

Danger label(s) 3



Special provisions (SP) 223

Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

EmS F-E, S-D

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 3



Special provisions (SP) A3

Excepted quantities (EQ) E1

Limited quantities (LQ) 10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
P5c	flammable liquids (cat. 2, 3)	5,000 50,000	51)

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08

Notation

51) flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive (2004/42/EC)

VOC content	59.46 % 590 g/l
-------------	--------------------

Industrial Emissions Directive (IED) (2010/75/EU)

VOC content	59.46 % 585.3 g/l
-------------	----------------------

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

none of the ingredients are listed

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on drug precursors

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

National regulations (GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

none of the ingredients are listed

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
PUR-Hardener 8429	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		3

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08:

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification (acc. to GB CLP): change in the listing (table)	yes
2.2		- Pictograms: change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
2.2		- Precautionary statements: change in the listing (table)	yes
2.2		- Hazardous ingredients for labelling: hexamethylene-1,6-diisocyanate, oligomers	yes
2.3	Other hazards	Other hazards: Keep out of reach of children and do not empty into the drains. Dispose remainders properly (collection of hazardous waste, disposal companies). Empty containers must be entered into the recycling system. The usual safety precautions must be observed during processing of the product.	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0,1\%$.	yes
4.1	Following inhalation: Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions.	Following inhalation: Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician.	yes
9.1	Solubility(ies): not determined	Solubility(ies)	yes
9.1		Water solubility: not miscible in any proportion	yes
11.1	Respiratory or skin sensitisation: Contains isocyanates. May produce an allergic reaction.	Respiratory or skin sensitisation: May cause an allergic skin reaction.	yes
11.1	Specific target organ toxicity - single exposure: Shall not be classified as a specific target organ toxicant (single exposure).	Specific target organ toxicity - single exposure: May cause respiratory irritation.	yes
13.1		- Product: change in the listing (table)	yes
15.1		List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list: none of the ingredients are listed	yes
15.1	Restrictions according to GB REACH, Annex 17: none of the ingredients are listed	Restrictions according to GB REACH, Annex 17	yes

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08:

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
16		Abbreviations and acronyms: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2019/1831/EU	Commission Directive establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
Acute Tox.	Acute toxicity
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GB CLP	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
GHS-GB	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08:

Abbr.	Descriptions of used abbreviations
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Sens.	Skin sensitisation
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended). The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended). GB mandatory classification and labelling.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.

Note concerning the lower explosion limit of water-thinnable varnishes:

See PTB research report PEx5 200500185, Physical-Technical Federal Agency Braunschweig, September 2005 and report PTB-W-57, February 1994.



Safety Data Sheet

acc. to GHS-GB

PUR-Hardener 8429

Version number: 2.0

Revision: 2024-01-08
Date of issue: 2024-01-08:

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.