

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **Pullex Renovier-Grund** **4416a:**
Different colours

Product number 4416057101 ff

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Coating material for commercial or consumer end-uses.

Uses advised against Any use not listed above.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

ADLER-Werk Lackfabrik Johann Berghofer GmbH & Co KG
Bergwerkstraße 22
A-6130 Schwaz
Austria

Telephone: +4352426922713
e-mail: sdb-info@adler-lacke.com

Further information obtainable from: sdb-info@adler-lacke.com

Telephone
+43 5242 6922-713
Mon - Thu 07:00 - 16:25
Fri 07:00 - 12:15

1.4 Emergency telephone number

| Country | Name | Telephone |
|---------|---|-----------------|
| Austria | Vergiftungsinformationszentrale (Poison Information Center) | +43 1 406 43 43 |

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

| Hazard class | Category | Hazard class and category | Hazard statement |
|---|----------|---------------------------|------------------|
| flammable liquid | 3 | Flam. Liq. 3 | H226 |
| hazardous to the aquatic environment - chronic hazard | 3 | Aquatic Chronic 3 | H412 |

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- Signal word warning

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:**- Pictograms**

GHS02

**- Hazard statements**H226 Flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.**- Precautionary statements**P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P273 Avoid release to the environment.
P280 Wear protective gloves/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents, container in accordance with national regulations.**- Supplemental hazard information**EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compds. with amides from diethylenetriamine and tall-oil fatty acids, 3-iodo-2-propynyl-butylcarbamate, Turpentine oil. May produce an allergic reaction.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.**2.3 Other hazards**

Cloths soaked in oxidatively drying products may ignite spontaneously! Unfold soaked cloths and allow to dry; storage in closed metal containers or under water necessary. . Keep out of reach of children and do not empty into the drains. Dispose remainders properly (collection of hazardous waste, disposal companies). Empty containers must be entered into the recycling system. The usual safety precautions must be observed during processing of the product.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Endocrine disrupting propertiesDoes not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.**SECTION 3: Composition/information on ingredients****3.1 Substances**

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Alkyd resins with pigments and other additives in organic solvents - contains film preservatives.

| Name of substance | Identifier | Wt% | Classification acc. to GHS |
|------------------------------|------------|-----------|----------------------------|
| Hydrocarbons, C10-C13, n-al- | EC No | 25 - < 50 | Asp. Tox. 1 / H304 |

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

| Name of substance | Identifier | Wt% | Classification acc. to GHS |
|---|--|-------------|--|
| kanes, isoalkanes, cyclics, < 2% aromatics | 918-481-9 REACH Reg. No 01-2119457273-39-xxxx | | |
| Titanium dioxide | CAS No 13463-67-7 EC No 236-675-5 Index No 022-006-00-2 REACH Reg. No 01-2119489379-17-xxxx | 10 – < 25 | Carc. 2 / H351 |
| (2-Methoxymethylethoxy)propanol | CAS No 34590-94-8 EC No 252-104-2 REACH Reg. No 01-2119450011-60-xxxx 01-2119991100-47-xxxx | 3 – < 5 | |
| Turpentine oil | CAS No 8006-64-2 EC No 232-350-7 Index No 650-002-00-6 REACH Reg. No 01-2119502456-45-xxxx | 0,5 – < 1 | Flam. Liq. 3 / H226 Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Skin Sens. 1 / H317 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411 |
| 3-iodo-2-propynylbutylcarbamate | CAS No 55406-53-6 EC No 259-627-5 Index No 616-212-00-7 REACH Reg. No 01-2120762115-60-xxxx | 0,1 – < 0,3 | Acute Tox. 4 / H302 Acute Tox. 3 / H331 Eye Dam. 1 / H318 Skin Sens. 1 / H317 STOT RE 1 / H372 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410 |
| Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compds. with amides from diethylenetriamine and tall-oil fatty acids | CAS No 222716-38-3 EC No 638-743-3 | 0,1 – < 0,3 | Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Skin Sens. 1 / H317 STOT RE 2 / H373 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410 |

| Name of substance | Specific Conc. Limits | M-Factors | ATE | Exposure route |
|---------------------------------|-----------------------|--------------------------|--|--------------------------------------|
| Turpentine oil | - | - | 500 mg/kg 1.100 mg/kg 13,7 mg/l/4h | oral dermal inhalation: vapour |
| 3-iodo-2-propynylbutylcarbamate | - | M-factor (acute) = 10 | 1.795 mg/kg >0,5 mg/l/4h | oral inhalation: dust/mist |
| Fatty acids, tall-oil, es- | - | - | 500 mg/kg | oral |

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

| Name of substance | Specific Conc. Limits | M-Factors | ATE | Exposure route |
|--|-----------------------|-----------|-----|----------------|
| ters with polyethylene glycol mono(hydrogen maleate), compds. with amides from diethylenetriamine and tall-oil fatty acids | | | | |

Remarks

For full text of abbreviations: see SECTION 16. This mixture contains $\geq 1\%$ titanium dioxide (CAS 13463-67-7). The Annex VI classification of Titanium dioxide does not apply to this mixture according to its Note 10.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Take off immediately all contaminated clothing. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Following inhalation

Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions.

Following skin contact

Take off contaminated clothing. After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Do not use any solvents or thinners!.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Keep at rest. IF SWALLOWED: Immediately call a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), BC-powder, Water spray, Alcohol resistant foam, Sand

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Thick smoke may occur in case of a fire. Inhaling the decomposed products may cause serious damage to health. The formation of explosive dust-air-mixtures is possible. Upon contact with air, the vapours may form an explosive mixture. . Combustible.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Provision of sufficient ventilation. Control of dust.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains, Fill contaminated material in the original container or any other suitable one and dispose it in accordance with point 13.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feed-stuffs.

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Protect from sunlight.

Control of effects

Do not pierce or burn, even after use. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Close the open container carefully and keep it straight to prevent leakage. Store in the original container. Storage temperature of 0 °C/32 °F and up to 50 °C/122 °F.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Occupational exposure limit values (Workplace Exposure Limits) | | | | | | | | | | | |
|--|---|------------|------------|-----------|--------------------------|------------|---------------------------|-----------------|--------------------------------|----------|------------|
| Country | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m ³] | STEL [ppm] | STEL [mg/m ³] | Ceiling-C [ppm] | Ceiling-C [mg/m ³] | Notation | Source |
| AT | Kohlenwasserstoffe, C10-C13, n-Alkane, Isoalkane, ringförmige Verbindungen, < 2% Aromaten | | MAK | | | | 1.200 | | | | |
| AT | titanium dioxide | 13463-67-7 | MAK | | 5 | | 10 (60 min) | | | r, dust | GKV |
| AT | dipropylene glycol monomethyl ether | 34590-94-8 | MAK | 50 | 307 | | | 100 (5 min) | 614 (5 min) | H | GKV |
| AT | silica, amorphous | 7631-86-9 | MAK | | 4 | | | | | i | GKV |
| AT | turpentine, oil | 8006-64-2 | MAK | 100 | 560 | | | 100 | 560 | H | GKV |
| EU | (2-methoxy-methylethoxy)propanol | 34590-94-8 | IOEL V | 50 | 308 | | | | | H | 2000/39/EC |

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur
dust as dust
H absorbed through the skin

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

Notation

| | |
|------|--|
| i | inhalable fraction |
| r | respirable fraction |
| STEL | short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) |
| TWA | time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) |

| Relevant DNELs of components | | | | | | |
|----------------------------------|------------|-----------|-------------------------|------------------------------------|-------------------|----------------------------|
| Name of substance | CAS No | End-point | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
| (2-Methoxymethyl-ethoxy)propanol | 34590-94-8 | DNEL | 308 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| (2-Methoxymethyl-ethoxy)propanol | 34590-94-8 | DNEL | 283 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | DNEL | 0,023 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | DNEL | 0,07 mg/m ³ | human, inhalatory | worker (industry) | acute - systemic effects |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | DNEL | 1,16 mg/m ³ | human, inhalatory | worker (industry) | chronic - local effects |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | DNEL | 1,16 mg/m ³ | human, inhalatory | worker (industry) | acute - local effects |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | DNEL | 2 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |

| Relevant PNECs of components | | | | | | |
|----------------------------------|------------|-----------|-----------------|-----------------------|------------------------------|------------------------------|
| Name of substance | CAS No | End-point | Threshold level | Organism | Environmental compartment | Exposure time |
| (2-Methoxymethyl-ethoxy)propanol | 34590-94-8 | PNEC | 19 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| (2-Methoxymethyl-ethoxy)propanol | 34590-94-8 | PNEC | 1,9 mg/l | aquatic organisms | marine water | short-term (single instance) |
| (2-Methoxymethyl-ethoxy)propanol | 34590-94-8 | PNEC | 4.168 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| (2-Methoxymethyl-ethoxy)propanol | 34590-94-8 | PNEC | 70,2 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |
| (2-Methoxymethyl-ethoxy)propanol | 34590-94-8 | PNEC | 7,02 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| (2-Methoxymethyl-ethoxy)propanol | 34590-94-8 | PNEC | 2,74 mg/kg | terrestrial organisms | soil | short-term (single instance) |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | PNEC | 0,001 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | PNEC | 0 mg/l | aquatic organisms | marine water | short-term (single instance) |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | PNEC | 0,44 mg/l | aquatic organisms | sewage treatment plant (STP) | short-term (single instance) |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | PNEC | 0,017 mg/kg | aquatic organisms | freshwater sediment | short-term (single instance) |

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

| Relevant PNECs of components | | | | | | |
|----------------------------------|------------|-----------|-----------------|-----------------------|---------------------------|------------------------------|
| Name of substance | CAS No | End-point | Threshold level | Organism | Environmental compartment | Exposure time |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | PNEC | 0,002 mg/kg | aquatic organisms | marine sediment | short-term (single instance) |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | PNEC | 0,005 mg/kg | terrestrial organisms | soil | short-term (single instance) |

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Use safety goggle with side protection (EN 166).

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Use protective gloves made of nitrile rubber as spray protection for short-term work. Material strength: 0.2mm, penetration time \geq 480 min

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment. Combination filtering device (EN 141). Particulate filter device (EN 143). Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|--|
| Physical state | liquid |
| Colour | different colours |
| Odour | characteristic |
| Melting point/freezing point | not determined |
| Boiling point or initial boiling point and boiling range | 186 °C at 1 atm |
| Flammability | flammable liquid in accordance with GHS criteria |

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

Lower and upper explosion limit

| | |
|-----------------------------|--------------------------------|
| Lower explosion limit (LEL) | 0,6 vol% |
| Upper explosion limit (UEL) | 14 vol% |
| Flash point | 46 °C |
| Auto-ignition temperature | >200 °C |
| pH (value) | not determined |
| Kinematic viscosity | 70 mm ² /s at 40 °C |

Solubility(ies)

| | |
|------------------|--------------------------------|
| Water solubility | not miscible in any proportion |
|------------------|--------------------------------|

Partition coefficient

| | |
|---|-----------------------------------|
| Partition coefficient n-octanol/water (log value) | this information is not available |
|---|-----------------------------------|

| | |
|-----------------|--------------------|
| Vapour pressure | 10 mmHg at 75,1 °C |
|-----------------|--------------------|

Density and/or relative density

| | |
|-------------------------|---|
| Density | 1,02 - 1,099 g/cm ³ at 20 °C |
| Relative vapour density | information on this property is not available |

| | |
|--------------------------|-----------------------|
| Particle characteristics | not relevant (liquid) |
|--------------------------|-----------------------|

Other safety parameters

| | |
|----------------------|---|
| Explosive properties | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
|----------------------|---|

9.2 Other information

| | |
|--|------------------------------------|
| Information with regard to physical hazard classes | there is no additional information |
| Other safety characteristics | there is no additional information |

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Heating may cause a fire. Cloths soaked in oxidatively drying products may ignite spontaneously! Unfold soaked cloths and allow to dry; storage in closed metal containers or under water necessary. .

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

| Acute toxicity estimate (ATE) of components | | | |
|---|-------------|-----------------------|--------------|
| Name of substance | CAS No | Exposure route | ATE |
| Turpentine oil | 8006-64-2 | oral | 500 mg/kg |
| Turpentine oil | 8006-64-2 | dermal | 1.100 mg/kg |
| Turpentine oil | 8006-64-2 | inhalation: vapour | 13,7 mg/l/4h |
| 3-iodo-2-propynylbutylcarbamate | 55406-53-6 | oral | 1.795 mg/kg |
| 3-iodo-2-propynylbutylcarbamate | 55406-53-6 | inhalation: dust/mist | >0,5 mg/l/4h |
| Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compds. with amides from diethylenetriamine and tall-oil fatty acids | 222716-38-3 | oral | 500 mg/kg |

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Contains Fatty acids, tall-oil, esters with polyethylene glycol mono(hydrogen maleate), compds. with amides from diethylenetriamine and tall-oil fatty acids, 3-iodo-2-propynylbutylcarbamate, Turpentine oil. May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Other information

Repeated exposure may cause skin dryness or cracking.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

| Aquatic toxicity (chronic) of components | | | | | |
|--|------------|----------|----------|----------------|---------------|
| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | ErC50 | 0,1 mg/l | algae | 120 h |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | EC50 | 44 mg/l | microorganisms | 3 h |

12.2 Persistence and degradability

| Degradability of components | | | | | | |
|---|------------|---------------------------|------------------|------|--------|--------|
| Name of substance | CAS No | Process | Degradation rate | Time | Method | Source |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | | oxygen depletion | 10 % | 5 d | | ECHA |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | | carbon dioxide generation | 0 % | 3 d | | ECHA |
| (2-Methoxymethylethoxy)propanol | 34590-94-8 | oxygen depletion | 75 % | 10 d | | ECHA |
| (2-Methoxymethylethoxy)propanol | 34590-94-8 | DOC removal | 96 % | 28 d | | ECHA |
| (2-Methoxymethylethoxy)propanol | 34590-94-8 | carbon dioxide generation | 76 % | 28 d | | ECHA |

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

| Degradability of components | | | | | | |
|----------------------------------|------------|---------------------------|------------------|------|--------|--------|
| Name of substance | CAS No | Process | Degradation rate | Time | Method | Source |
| oxy)propanol | | tion | | | | |
| 3-iodo-2-propynyl-butylcarbamate | 55406-53-6 | carbon dioxide generation | 4 % | 1 d | | ECHA |

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes, Decision 2000/532/EC on the list of waste

- Product
08 01 11* waste paint and varnish containing organic solvents or other hazardous substances
- Product residues
15 01 10* packaging containing residues of or contaminated by hazardous substances
- Packagings
15 01 02 plastic packaging
15 01 04 metallic packaging

List of wastes (ÖNORM S 2100)

55502: Altlacke, Altfarben, soferne lösemittel- und/oder schwermetallhaltig, sowie nicht voll ausgehärtete Reste in Gebinden.

- Restentleerte Verpackungen (ja nach angeführtem Recyclingcode gemäß der Richtlinie 94/62/EG auf der Verpackung)

35105: Eisenmetalleballagen (Recyclingcode FE40).

57118: Kunststoffemballagen und -behältnisse (Recyclingcodes: PET01, PE-HD02, PE-LD04 oder PP05).

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

Disposal methods:

Product

Waste production should be avoided or minimised if possible.

Do not empty into the drains. Avoid releasing the product into the environment. Waste, containers must be removed, disposed in a safe way.

Packagings

Waste production should be avoided or minimised if possible.

Packaging waste should be recycled. Burning or landfilling should only be considered if recycling is not feasible.

Notes on disposal:

Product

Disposal of this product and its dissolutions and by-products must be carried out in accordance with the environmental protection requirements and waste disposal laws as well as the requirements of the local authorities at all times. Excess must be handed over, disposed to a recognised waste disposal company (disposal company/recycling company).

Packagings

With the aid of the information provided in this safety data sheet, the responsible authorities must be consulted regarding classification of empty containers, packaging. Empty containers should be disposed, recycled according to type. Licenced containers, packaging can be disposed free of charge via system partners, where applicable. Containers with residual contents must be disposed in accordance with local and national legal provisions.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number

| | |
|-------------|---------|
| ADR/RID/ADN | UN 1263 |
| IMDG-Code | UN 1263 |
| ICAO-TI | UN 1263 |

14.2 UN proper shipping name

| | |
|-------------|-------|
| ADR/RID/ADN | PAINT |
| IMDG-Code | PAINT |
| ICAO-TI | Paint |

14.3 Transport hazard class(es)

| | |
|-------------|---|
| ADR/RID/ADN | 3 |
| IMDG-Code | 3 |
| ICAO-TI | 3 |

14.4 Packing group

| | |
|-------------|-----|
| ADR/RID/ADN | III |
| IMDG-Code | III |
| ICAO-TI | III |

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

| | |
|---|---------------|
| Classification code | F1 |
| Danger label(s) | 3 |
|  | |
| Special provisions (SP) | 163, 367, 650 |
| Excepted quantities (EQ) | E1 |
| Limited quantities (LQ) | 5 L |
| Transport category (TC) | 3 |
| Tunnel restriction code (TRC) | D/E |
| Hazard identification No | 30 |

International Maritime Dangerous Goods Code (IMDG) - Additional information

| | |
|---|--------------------|
| Marine pollutant | - |
| Danger label(s) | 3 |
|  | |
| Special provisions (SP) | 163, 223, 367, 955 |
| Excepted quantities (EQ) | E1 |
| Limited quantities (LQ) | 5 L |
| EmS | F-E, <u>S-E</u> |
| Stowage category | A |

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

| | |
|---|---------------|
| Danger label(s) | 3 |
|  | |
| Special provisions (SP) | A3, A72, A192 |
| Excepted quantities (EQ) | E1 |
| Limited quantities (LQ) | 10 L |

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

Seveso Directive

| 2012/18/EU (Seveso III) | | | | |
|-------------------------|---------------------------------------|---|--------|-------|
| No | Dangerous substance/hazard categories | Qualifying quantity (tonnes) for the application of lower and upper-tier requirements | | Notes |
| P5c | flammable liquids (cat. 2, 3) | 5.000 | 50.000 | 51) |

Notation

51) flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive (2004/42/EC)

| | |
|-------------|--------------------|
| VOC content | 45,91 % 500 g/l |
|-------------|--------------------|

Industrial Emissions Directive (IED) (2010/75/EU)

| | |
|-------------|----------------------|
| VOC content | 44,94 % 493,9 g/l |
|-------------|----------------------|

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Water Framework Directive (WFD)

| List of pollutants (WFD) | | | |
|--------------------------|--------|-----------|---------|
| Name of substance | CAS No | Listed in | Remarks |
| Titanium dioxide | | a) | |
| Titanium dioxide | | a) | |

Legend

a) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on drug precursors

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

Biocidal active substances

| Name of substance | % (W/w) | Unit |
|---------------------------------|---------|------|
| 3-iodo-2-propynylbutylcarbamate | 2,4 | g/kg |

National regulations (Austria)

Ordinance on combustible liquids (VbF) not applicable

- VbF (group and hazard class) not applicable

National regulations (Germany)

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 2 obviously hazardous to water
(water hazard class)

Storage of hazardous substances in non-stationary containers (TRGS 510) (Germany)

Storage class (LGK) 3 (flammable or desensitizing explosive liquids)

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

| Section | Former entry (text/value) | Actual entry (text/value) | Safety-relevant |
|---------|---|--|-----------------|
| 2.3 | Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0,1\%$. | Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$. | yes |
| 3.2 | | Description of the mixture: change in the listing (table) | yes |
| 3.2 | | Remarks: For full text of abbreviations: see SECTION 16. This mixture contains $\geq 1\%$ titanium dioxide (CAS 13463-67-7). The Annex VI classification of Titanium dioxide does not apply to this mixture according to its Note 10. | yes |
| 8.2 | Hand protection: Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Use protective gloves made of butyl rubber as spray protection for short-term work. Material strength: 0.5mm, penetration time ≥ 480 min. | Hand protection: Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Use protective gloves made of nitrile rubber as spray protection for short-term work. Material strength: 0.2mm, penetration time ≥ 480 min | yes |
| 11.1 | | Acute toxicity estimate (ATE) of components: change in the listing (table) | yes |
| 13.1 | | - Product residues: change in the listing (table) | yes |
| 13.1 | | - Packagings: | yes |

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

| Section | Former entry (text/value) | Actual entry (text/value) | Safety-relevant |
|---------|--|--|-----------------|
| | | change in the listing (table) | |
| 13.1 | List of wastes (ÖNORM S 2100): 55502: Altlacke, Altfarben, soferne lösemittel- und/oder schwermetallhaltig, sowie nicht voll ausgehärtete Reste in Gebinden. 55503: Lack- und Farbschlamm. | List of wastes (ÖNORM S 2100): 55502: Altlacke, Altfarben, soferne lösemittel- und/oder schwermetallhaltig, sowie nicht voll ausgehärtete Reste in Gebinden.- Restentleerte Verpackungen (ja nach angeführtem Recyclingcode gemäß der Richtlinie 94/62/EG auf der Verpackung) 35105: Eisenmetalleballagen (Recyclingcode FE40). 57118: Kunststoffemballagen und -behälter (Recyclingcodes: PET01, PE-HD02, PE-LD04 oder PP05). | yes |
| 15.1 | VOC content: 45,91 % 510 g/l | VOC content: 45,91 % 500 g/l | yes |
| 15.1 | Storage class (LGK): 3 (flammable and desensitizing explosive liquids) | Storage class (LGK): 3 (flammable or desensitizing explosive liquids) | yes |

Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|-----------------|---|
| 2000/39/EC | Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC |
| Acute Tox. | Acute toxicity |
| ADN | Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) |
| ADR | Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road) |
| ADR/RID/ADN | Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN) |
| Aquatic Acute | Hazardous to the aquatic environment - acute hazard |
| Aquatic Chronic | Hazardous to the aquatic environment - chronic hazard |
| Asp. Tox. | Aspiration hazard |
| ATE | Acute Toxicity Estimate |
| Carc. | Carcinogenicity |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| Ceiling-C | Ceiling value |
| CLP | Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| DNEL | Derived No-Effect Level |
| EC50 | Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval |
| EC No | The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union) |

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

| Abbr. | Descriptions of used abbreviations |
|-------------|--|
| ED | Endocrine disruptor |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| ELINCS | European List of Notified Chemical Substances |
| EmS | Emergency Schedule |
| ErC50 | ≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control |
| Eye Dam. | Seriously damaging to the eye |
| Eye Irrit. | Irritant to the eye |
| Flam. Liq. | Flammable liquid |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |
| GKV | Grenzwerteverordnung |
| IATA | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| ICAO-TI | Technical instructions for the safe transport of dangerous goods by air |
| IMDG | International Maritime Dangerous Goods Code |
| IMDG-Code | International Maritime Dangerous Goods Code |
| index No | The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 |
| IOELV | Indicative occupational exposure limit value |
| LGK | Lagerklasse (storage class according to TRGS 510, Germany) |
| M-factor | Means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present |
| NLP | No-Longer Polymer |
| PBT | Persistent, Bioaccumulative and Toxic |
| PNEC | Predicted No-Effect Concentration |
| ppm | Parts per million |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| RID | Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail) |
| Skin Corr. | Corrosive to skin |
| Skin Irrit. | Irritant to skin |
| Skin Sens. | Skin sensitisation |
| STEL | Short-term exposure limit |
| STOT RE | Specific target organ toxicity - repeated exposure |
| SVHC | Substance of Very High Concern |
| TRGS | Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany) |
| TWA | Time-weighted average |
| VbF | Ordinance on combustible liquids (Austria) |

Pullex Renovier-Grund

Version number: 27.0

Revision: 18.03.2025
Date of issue: 18.03.2025:

| Abbr. | Descriptions of used abbreviations |
|-------|--|
| VOC | Volatile Organic Compounds |
| vPvB | Very Persistent and very Bioaccumulative |

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|------|--|
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H351 | Suspected of causing cancer. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

Note concerning the lower explosion limit of water-thinnable varnishes:

See PTB research report PEx5 200500185, Physical-Technical Federal Agency Braunschweig, September 2005 and report PTB-W-57, February 1994.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.